

COMPACT 50L SMART THINGS COME IN SMALL PACKAGES

Designed to be everything you asked for in a compact water heater, the 50 Litre Electric is MEPS compliant.

We solved the access problem by relocating all the service outlets to the front and unlike some units, ours have remained smaller in size.





160L SQUAT A BIG TANK MADE FOR SHORT SPACES

The AquaMAX commitment to innovation continues with the 160 Litre Electric Squat. An Electric Water Heater that brings larger capacity to awkward indoor spaces. With dual inlets and outlets, the 160 Litre Electric Squat brings reliable delivery in a smarter package.



250L-400L ELECTRICS **BIG DELIVERY, LOWER RUNNING COSTS**

The AquaMAX large Electric water heater range provides an option to take advantage of lower cost off-peak tariffs.² Built with dual inlets and outlets (like the rest of the range), the 250-400 Litre Electric range is available in single or twin element models.

Water Heater Dimensions (mm)	н	A	В	D
991050	695	539	142	400
981080	875	669	194	460
981125	1250	1047	195	480
971160	1610	1436	104	480
9W1160	965	755	113	640
991250/992250	1395	1190	73	640
991315/992315	1640	1430	113	640
991400/992400	1840	1600	121	690

Aquamax Australia Pty Ltd 463-467 Warrigal Road Moorabbin Vic 3189 Toll Free: 131 031 Sales Ph: 132 552 Sales Fax: 1300 554 821 Email: sales@aquamax.com.au For more information visit www.aquamax.com.au



Electri



A.B.N. 37 138 189 689



Julv 2018 Part No. AQ0905040-J

VITREOUS ENAMEL ELECTRIC WATER HEATERS



AX Electric auaN ter Heaters... ou more g water" hoi

Stay in hot water with AquaMAX.

Award winning AquaMAX high efficiency Electric Water Heaters provide your family with all the hot water they need.

AquaMAX Mains Pressure Electric Water Heaters are built using the latest technology and backed by a 10 or 7 year cylinder warranty.¹ They are available in sizes to suit most applications.

AquaMAX Electric Water Heaters are made for Aussie conditions, to suit both metro and regional areas.

FAMILIES BIG AND SMALL

AquaMAX Electric Mains Pressure Water Heaters provide families big and small with reliable hot water. AquaMAX inhouse factory testing ensures every new system we build meets our exacting standards whether it's installed indoors or outdoors. You can also take advantage of lower cost off-peak tariffs for added savings on your energy bills.²

HOW DO WE MAKE THEM ACHIEVE OUR STANDARD?

After our cylinders have been fully welded, we apply a high quality enamel coating to create our enamel lining. Combined with a sacrificial anode and protected by a steel casing with rounded edges, every AquaMAX Electric Water Heater is backed by a 10 or 7 year cylinder warranty.¹

		4	400 Litre			315 Litre			250 Litre			160 Litre Squat		160 Litre			125 Litre			80 Litre	50 Litre	
Electric Specifications		991400G7	991400G8	992400G8	991315G7	991315G8	992315G7	992315G8	991250G7	991250G7/BL	991250G8	992250G7	9W1160G4	9W1160G5	971160G4	971160G5	971160G7	981 125G4	981125G4/BL	981125G7	981080G7	991050G7
Number of People Serviced - Continuous/Time of Use Ta	riff		5-9			4	-6			3.	-5		2.	-4		2-4			2-3		1-2	1
- Off peak/night rate			4-6			2	-4			1-	-3		-	-		-			-		-	-
Hot Water Delivery	Litres		400			3	15			25	50		16	50		160			125		80	50
Boost Capacity (Twin Element)	Litres	-	_	90	-	_	5	0		-		50	-	_		-			-		-	-
Weight packaged (approx)	kg		120			9	7			8	2		5	8		59			45		32	26
Maximum Loading	Watts	3600	4800	4800	3600	4800	3600	4800	3600	3600	4800	3600	1800	2400	1800	2400	3600	1800	1800	3600	3600	3600
Heating Element Upper	Watts	-	-	4800	-	-	3600	4800		-		3600	-	-		-			-			-
Heating Element Lower	Watts	3600	4800	4800	3600	4800	3600	4800	3600	3600	4800	3600	1800	2400	1800	2400	3600	1800	1800	3600	3600	3600
									100		A.	A COL		1000	AT	6						



Specifications	991400	991315	991250	9W1160	971160	981125	981080	991050		
Voltage (single phase)	240Vac	240Vac			2	40Vac	240Vac			
Maximum Supply Pressure										
with expansion control valve (ECV)	680 kPa		580 kPa	3	960 kPa 680 kPa) kPa	960 kPa		
without expansion control valve (ECV)	800 kPa	800 kPa		1120 kPa	800 kPa		1120 kPa			
Pressure & Temp Relief Valve	1000 kPa	1000 kPa			1400 kPa	1000 kPa		1400 kPa		
ECV setting	850 kPa	850 kPa			1200 kPa	850) kPa	1200 kPa		
Thermostat setting (Maximum)	70°C	70°C				70°C	75°C			
Hot & Cold Water connection	Rp 3/4" Female	Rp 3	7/4" Female Rp 3/4" Female		p 3/4" Female Rp 3/-		Rp 3/4" Female		lle	Rp 3/4" Female
Warranty (Cylinder) ¹	10 years*	1	0 years	*	10) years*	7 years†			
Warranty (Parts & Labour) ¹	1 year	1 year			1	l year	1 year			
Protection rating	IP24		IP24			IP24		IP24		

Due to constant product improvements, the specifications are subject to change without notice. 1. Conditions apply. Full warranty details available on request from AquaMax, call Toll Free 131 031, see the warranty set out in the Owner's Guide and Installation Instructions or view at www.aquamax.com.au

[†] 7 year cylinder warranty applies to – 991050 model manufactured on or after 01/3/2018. 2. Please refer to your energy provider.



* 10 year cylinder warranty applies to - 991400, 992400, 991315, 992315, 991250, 992250 models manufactured on or after 20/11/2017, 971160 model manufactured on or after 10/4/2018, 981125, and 981080 models manufactured on or after 01/3/2018.